

TVP5150A Quick Start Guide

Digital Audio/Video

ABSTRACT

The TVP5150A is a low-power NTSC/PAL/SECAM decoder in a small 32-pin TQFP package. It is a highly programmable device suitable for a broad range of video applications, but is designed for maximum ease of use. This document includes information to help the user design with the TVP5150A and understand some of its capabilities and requirements.

Contents

TVP5150A Example Application	2
TVP5150A Input Termination and Gain Range.....	4
Antialias Filtering.....	5
Crystal Circuit Design.....	7
Minimum Register Initialization	8
References	8

Figures

Figure 1. TVP5150A Example Application	3
Figure 2. 75-Ω Terminated Composite Signal Amplitude	4
Figure 3. TVP5150 Input Termination.....	4
Figure 4. Example Antialias Filters for Composite and S-Video	5
Figure 5. Example Antialias Filter Characteristics.....	6
Figure 6. Crystal Circuit.....	7

Tables

Table 1. AGC Range for Common Resistor-Divider Terminations	5
Table 2. Example Antialias Filter Characteristics (Detail).....	7
Table 3. Example Register Initialization of TVP5150A.....	8

TVP5150A Example Application

Figure 1 shows an example of how to connect the TVP5150A in a simple application. The example application shows how external analog switches can be used to allow multiple inputs on each of the two analog video input pins of the TVP5150A. The example shows how the GPCL output of the TVP5150A can be used to select between the inputs to the analog switches. (The state of the GPCL output can be programmed using the I²C interface to the TVP5150A.) Optional antialias filters are also shown in the example.

The TVP5150A in the example is configured to output embedded synchronization signals in the video data stream on the YOUT[7:0] pins. This output format is described in the ITU-R BT.656 standard and does not require the use of the discrete synchronization signals on pins VSYNC, HSYNC, FID, AVID. These discrete synchronization signals can optionally be enabled and connected for applications requiring them.

The TVP5150A I²C base address selected with pulldown resistor R7 is B8.




Figure 1. TVP5150A Example Application

TVP5150A Input Termination and Gain Range

Figure 2 shows a standard composite video signal with maximum allowable chroma excursion, terminated with a standard 75-Ω load. Maximum chroma excursion is demonstrated with a 100% amplitude, 100% saturation color bar test pattern. The maximum amplitude for a signal terminated by 75 Ω is 1.24 V, which exceeds the TVP5150A maximum input level of 0.75 V.




Figure 2. 75-Ω Terminated Composite Signal Amplitude

Figure 3 shows the recommended input termination circuit for the TVP5150A. A resistor divider network is used to attenuate the input signal while still providing a termination of approximately 75 Ω. Recommended attenuation is 50%, achieved with two commonly available 39-Ω resistors. The recommended ac-coupling capacitor value is 0.1 μF.




Figure 3. TVP5150 Input Termination

The automatic gain control of the TVP5150A properly scales inputs with amplitudes of approximately 30-135% amplitude when the recommended resistor-divider termination is used. Other resistor-divider pairs are possible, which result in different effective ranges for automatic gain control. Table 1 shows how the AGC range changes for different termination pairs.

NOTE: Due to the 0.75-Vp-p input limit, the upper end of each amplitude range includes certain signals (example: 100% amplitude, 100% saturation color bars), which exceed the range of the TVP5150A input circuit.

Table 1. AGC Range for Common Resistor-Divider Terminations

Resistor Pair R1:R2	Attenuation	Approx. AGC Range	Notes
56:18	24%	65-280%	Worse SNR
56:22	28%	55-240%	
47:27	36%	45-185%	
39:33	46%	35-145%	
39:39	50%	30-135%	Recommended termination
33:39	54%	30-125%	
27:47	64%	25-105%	Better SNR

Antialias Filtering

Antialias filtering may be required if out-of-band noise is present on the inputs to the TVP5150A. Figure 4 shows two example filters with good cost/performance characteristics for typical applications. A different filter is shown for S-video because the TVP5150A sample rate for each S-video component is 13.5 MHz, compared to 27 MHz for composite video. Similarly effective noise attenuation therefore requires a steeper rolloff and a higher-order filter.

The example S-video filter is shown in a form which can be implemented in two stages, separated by a switch so that only the second stage is used for composite video input. If a two-stage approach is not desired then the 470-pF/180-pF capacitor pair can be replaced in the design with a single 680-pF capacitor.

Figure 5 and Table 2 show amplitude and group delay characteristics for the example filters of Figure 4.




Figure 4. Example Antialias Filters for Composite and S-Video




Figure 5. Example Antialias Filter Characteristics

Table 2. Example Antialias Filter Characteristics (Detail)

Frequency (MHz)	Composite Filter		S-Video Filter		Notes
	Amplitude	Delay	Amplitude	Delay	
3.58		3 ns		11 ns	NTSC color subcarrier
4.2	-0.1 dB	4 ns	-0.1 dB	16 ns	NTSC bandwidth
4.43		4 ns		19 ns	PAL color subcarrier
6.0	-0.5 dB	7 ns	-1.3 dB	38 ns	PAL-D bandwidth
7.5	-1.1 dB		-5.4 dB		PAL sampled image for S-video
9.3	-2.7 dB		-13 dB		NTSC sampled image for S-video
21.0	-18 dB		-47 dB		PAL sampled image for composite
22.8	-20 dB		-51 dB		NTSC sampled image for composite

Crystal Circuit Design

Figure 6 shows an example reference clock circuit for the TVP5150A. Special care must be taken when using a crystal circuit to generate the reference clock for the TVP5150A. Small variations in reference clock frequency cause color to become intermittent or to go away altogether. Use the following guidelines to ensure correct reference clock operation:

- Use the right frequency crystal. The correct frequency is 14.31818 MHz. Tolerance should be 50 ppm or better.
- Use a parallel-resonant crystal. A series-resonant crystal oscillates in a parallel circuit, but at an incorrect frequency.
- Know the C_{load} for the crystal part number selected. The values of capacitors C1 and C2 must be matched to the C_{load} for the specific crystal part number in the user's system. Use the following formula:

$$C1 = C2 = 2C_{load} - C_{stray} \quad \text{where } C_{stray} \text{ is 3-8 pF, depending on board traces}$$

Example: $C_{load} = 20 \text{ pF}$. $C1 = 33 \text{ pF}$, $C2 = 33 \text{ pF}$




Figure 6. Crystal Circuit

Minimum Register Initialization

The TVP5150A is highly programmable; however, the device can be fully operational for most applications with very few register initializations. Table 3 shows a complete required register initialization to support the example application in Figure 1. The register settings in Table 3 (along with the default settings in all other registers) configure the example TVP5150A application to:

- Select the composite video input connected through the analog switch to TVP5150A input AIP1A
- Support automatic switching between multiple input standards
- Use embedded syncs in the output data stream (ITU-R BT.656)

No other register accesses are required to use the example application in this mode. All other registers can be left in their default states.

Table 3. Example Register Initialization of TVP5150A

Address	Data	Note
0x03	0x29	YUV output enable, GPCL output enable
0x0F	0x0A	Pin 27 is GPCL (for controlling external analog switch)

References

1. *TVP5150A Ultralow-Power NTSC/PAL/SECAM Video Decoder With Robust Sync Detector* data manual, SLES087

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		Applications	
Amplifiers	amplifier.ti.com	Audio	www.ti.com/audio
Data Converters	dataconverter.ti.com	Automotive	www.ti.com/automotive
DSP	dsp.ti.com	Broadband	www.ti.com/broadband
Interface	interface.ti.com	Digital Control	www.ti.com/digitalcontrol
Logic	logic.ti.com	Military	www.ti.com/military
Power Mgmt	power.ti.com	Optical Networking	www.ti.com/opticalnetwork
Microcontrollers	microcontroller.ti.com	Security	www.ti.com/security
		Telephony	www.ti.com/telephony
		Video & Imaging	www.ti.com/video
		Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments
Post Office Box 655303 Dallas, Texas 75265

Copyright © 2003, Texas Instruments Incorporated